

IN THE CLAIMS

1. (Currently Amended) A method comprising:
determining whether a digital signal processor needs a service program stored in a ~~juke box~~ an overlay memory; and
delivering the service program to the digital signal processor from the ~~juke box~~ overlay memory over a host port interface bus.
2. (Original) The method of claim 1, further comprising generating a data packet from a pulse code modulated data stream using the service program.
3. (Original) The method of claim 2, further comprising receiving the pulse code modulation data stream from a public switched telephone network.
4. (Original) The method of claim 2, further comprising:
transmitting the data packet over an internet protocol network.
5. (Currently Amended) The method of claim 1, ~~wherein the service program provides a service selected from the group comprising~~ 2, wherein the data packet includes data comprising at least one of voice communication, fax communication, modem communication, video communication, and audio communication.
6. (Original) The method of claim 1, further comprising:
receiving a packet from an internet protocol network;
generating a pulse code modulation data stream from the packet using the service program; and

transmitting the pulse code modulation data stream over a public switched telephone network.

7. (Currently Amended) An apparatus comprising:
 - means for determining whether a digital signal processor needs a service program stored in ~~a juke box~~ an overlay memory; and
 - means for delivering the service program to the digital signal processor from the ~~juke box~~ overlay memory over a host port interface bus.
8. (Original) The apparatus of claim 7, further comprising means for generating a data packet from a pulse code modulated data stream using the service program.
9. (Original) The apparatus of claim 8, further comprising means for receiving the pulse code modulation data stream from a public switched telephone network.
10. (Original) The apparatus of claim 8, further comprising:
 - means for transmitting the data packet over an internet protocol network.
11. (Currently Amended) The apparatus of claim 7, ~~wherein the service program provides a service selected from the group comprising~~ 8, wherein the data packet includes data comprising at least one of voice communication, fax communication, modem communication, video communication, and audio communication.
12. (Original) The apparatus of claim 7, further comprising:
 - means for receiving a packet from an internet protocol network;

means for generating a pulse code modulation data stream from the packet using the service program; and

means for transmitting the pulse code modulation data stream over a public switched telephone network.

13. (Currently Amended) A computer readable medium having instructions which, when executed by a processing system, cause the system to:

determine whether a digital signal processor needs a service program stored in a ~~juke-box~~ an overlay memory; and

deliver the service program to the digital signal processor from the ~~juke-box~~ overlay memory over a host port interface bus.

14. (Original) The medium of claim 13, wherein the executed instructions further cause the system to generate a data packet from a pulse code modulated data stream using the service program.

15. (Original) The medium of claim 14, wherein the executed instructions further cause the system to:

receive the pulse code modulation data stream from a public switched telephone network.

16. (Original) The medium of claim 14, wherein the executed instructions further cause the system to:

transmit the data packet over an internet protocol network.

17. (Original) The medium of claim 13, wherein the service program provides a service selected from the group comprising voice communication, fax communication, modem communication, video communication, and audio communication.
18. (Original) The medium of claim 13, wherein the executed instructions further cause the system to:
- receive a packet from an internet protocol network;
 - generate a pulse code modulation data stream from the packet using the service program; and
 - transmit the pulse code modulation data stream over a public switched telephone network.
19. (Currently Amended) An apparatus comprising:
- an interface manager to determine whether a digital signal processor needs a service program stored in a ~~juke-box~~ an overlay memory; and
 - a host port interface bus to deliver the service program to the digital signal processor from the ~~juke-box~~ overlay memory.
20. (New) The apparatus of claim 19, further comprising the overlay memory, the overlay memory to store a plurality of algorithms.
21. (New) The apparatus of claim 20, further comprising the digital signal processor.
22. (New) The apparatus of claim 21, further comprising a plurality of the digital signal processor coupled to the host port interface bus.

23. (New) The apparatus of claim 22, further comprising a packet pump comprising:
the interface manager; and
a host port interface bus manager coupled to the host port interface bus.
24. (New) The apparatus of claim 23, further comprising a public switched telephone network coupled to transmit a pulse code modulation data stream to the packet pump.
25. (New) The apparatus of claim 23, wherein the overlay memory is a static random access memory.
26. (New) The method of claim 1, wherein the overlay memory stores the service program and a plurality of other services programs, and wherein determining further comprises determining which of the service program and the plurality of other service programs are needed by the digital signal processor.
27. (New) The method of claim 26, wherein the service program comprises an algorithm and wherein delivering comprises downloading the algorithm to the digital signal processor.